

WALL WASH LIGHTS

30W - 45W - 90W

Fudakin™ Wall Wash Lights are a must for every outdoor application where surface lighting is required. These light fixtures provide excellent coverage and are designed to highlight the aesthetics of building architecture and signage.



FEATURES

- Outstanding optical design providing an efficient light source
- Anti-glare design during evening use enabling high safety rating
- Extrude aluminum with anodized surface treatment creates a state-of-the-art heat sink
- High lumen output is ideal for illuminating building facade and adjacent grounds
- Attractive styling and durability
- Suitable for wet locations
- Wide input voltage, AC100 – 277V
- Available in 30W, 45W and 90W
- cULus and DLC certified
- Suitable for use in a variety of temperate conditions
- Corrosion resistant design
- Contains no mercury

BENEFITS

- Saves up to 60% energy consumption compared to traditional lighting
- Easy installation
- Maintenance free
- High quality and reliability
- Even light distribution
- Long life

APPLICATIONS

- Wall Wash Lights are highly utilized on the exterior of office and warehouse buildings
- Also utilized extensively on the exterior walls of large retail stores and malls where retail traffic is present



WALL WASH LIGHTS

30W - 45W - 90W

Product Parameters

MODEL	Watts	Input Voltage	Luminous Flux	CCT	CRI	Beam Angle	Warranty	Working Temp.	Material
FDK-WW-02-30-XXK-YYYY-Z	30	100 - 277V	≥1000lm	3000K 4000K 5000K	≥80	10° x 50° 80° x 80°	5 Years	-40 - 50°C	Aluminum
FDK-WW-03-45-XXK-YYYY-Z	45		≥1600lm						
FDK-WW-06-90-XXK-YYYY-Z	90		≥3200lm						

Product Order Code

FDK-WW-X-XX-XXK-YYYY-Z

Product Series	Size	Wattage	CCT	Beam Angle	Dimmable
WW - Wall Wash	02 - 2 FT 03 - 3 FT 06 - 6 FT	30 - 30 watt 45 - 45 watt 90 - 90 watt	3K - 3000K 4K - 4000K 5K - 5000K	1050 - 10° x 50° 8080 - 80° x 80°	D - Dimmable N - Non Dimmable

Product Dimensions

Model Number	A (mm)	B (mm)	C (mm)
FDK-WW-02-30-XXK-YYYY-Z	609.6	83.4	88
FDK-WW-03-45-XXK-YYYY-Z	914.4	83.4	88
FDK-WW-06-90-XXK-YYYY-Z	1828.8	83.4	88

